Date: April, 28, 2009

Dear Dr. Arias, BIPM,

Attached is the report on the frequency measurement by NMIJ-F1, a cesium atomic fountain frequency standard of NMIJ, during **MJD 54919-54949.** The uncertainty evaluation was the same as that in the last publication.

Shinya Yanagimachi Akifumi Takamizawa Takeshi Ikegami

National Metrology Institute of Japan (NMIJ) Time and Frequency Division Time Standards Section AIST Tsukuba Central 3, Tsukuba-Shi, Ibaraki-Ken 305-8563, Japan

## Frequency comparison between H-Maser(405002) and Cs Fountain(NMIJ-F1) during MJD 54919-54949

The frequency of our Hydrogen maser HM(Clock # 405002) have been measured using NMIJ-F1 during MJD 54919-54949 (30 days). The results are shown in tables 1.

Period	54919-54949
Measurement ratio	98.5%
Y(NMIJ-F1)-Y(Maser 405002)	-201.1
<i>u</i> <sub>A</sub>	0.7
<i>u</i> <sub>B</sub>	3.9
<i>u</i> <sub>link / lab</sub>	0.3

Table 1. Results of the comparison in  $1 \times 10^{-15}$  unit.

## 1. Type A uncertainty $u_A$

The frequency stability  $\sigma_y(\tau)$  is  $1 \times 10^{-12} \tau^{-1/2}$ . This equation has been used for the estimation of type A uncertainty on the basis of white FM noise. The measurement uncertainty is  $0.7 \times 10^{-15}$ .

## 2. Uncertainty of the link in the laboratory $u_{link/lab}$

The uncertainty of the link in the laboratory,  $u_{link/lab}$ , is written as,

$$u_{link / lab} = \sqrt{u_{dead \ time}^2 + u_{link / maser}^2} \tag{1}$$

where  $u_{link/maser}$  is the uncertainty due to the phase noise of the synthesis chain between the fountain and HM,  $u_{dead \ time}$  is the uncertainty due to the operational dead time of the fountain.  $(u_{link/maser}, u_{dead \ time})$  are evaluated to be  $(2 \times 10^{-16}, 2 \times 10^{-16})$ . 3. Type B uncertainty  $u_B$ 

The value of type B uncertainty is the same as the last publication, as is shown in table 2.

MJD 34919-34949 III 1×10 uIIIt.		
Source of uncertainty	Bias	Uncertainty
2 <sup>nd</sup> order Zeeman	174.7	0.5
Blackbody radiation	-18.0	1.4
Gravitation	1.6	0.1
Cold collisions	0.0	3.3
Distributed cavity phase	0.0	1.2
Microwave power dependence	0.0	0.7
Total	158.3	3.9

Table 2: Frequency biases and uncertainties in NMIJ-F1 during the period MJD 54919-54949 in  $1 \times 10^{-15}$  unit.