

BUREAU INTERNATIONAL DES POIDS ET MESURES
ORGANISATION INTERGOUVERNEMENTALE DE LA CONVENTION DU METRE
PAVILLON DE BRETEUIL F-92312 SEVRES CEDEX TEL. +33 1 45 07 70 70 FAX. +33 1 45 34 20 21 tai@bipm.org

1 - Coordinated Universal Time UTC and its local realizations UTC(k). Computed values of $[UTC-UTC(k)]$ and uncertainties valid for the period of this Circular. From 2009 January 1, 0h UTC, $TAI-UTC = 34$ s.

Date 2010	0h UTC	SEP 30	OCT 5	OCT 10	OCT 15	OCT 20	OCT 25	OCT 30	Uncertainty/ns			Notes
MJD		55469	55474	55479	55484	55489	55494	55499	u_A	u_B	u	
Laboratory	k	$[UTC-UTC(k)]/ns$										
AOS	(Borowiec)	2.6	1.7	-1.0	-1.9	-3.4	-3.9	-3.8	0.5	5.2	5.2	
APL	(Laurel)	-8.3	-5.4	-7.5	-7.3	-9.7	-10.9	-2.6	1.5	5.2	5.4	
AUS	(Sydney)	146.3	151.7	158.3	165.7	170.9	180.9	196.2	0.4	5.1	5.1	
BEV	(Wien)	-0.6	-3.5	-3.5	-0.8	-7.6	-16.1	-15.1	1.5	3.2	3.6	
BIM	(Sofiya)	-6540.6	-6543.3	-6526.0	-6501.5	-6486.0	-6474.7	-6474.1	2.0	7.1	7.4	
BIRM	(Beijing)	-11601.2	-11633.9	-11675.2	-11719.5	-11759.1	-11799.4	-11830.4	2.0	20.0	20.1	
BY	(Minsk)	-27.8	-16.4	-7.4	1.3	5.3	10.1	13.1	2.0	7.1	7.4	
CAO	(Cagliari)	-4660.6	-4680.1	-4697.8	-4708.1	-4722.4	-4742.6	-4740.8	1.5	7.0	7.2	
CH	(Bern)	7.5	4.6	3.8	2.8	5.2	6.1	5.0	0.6	1.6	1.7	
CNM	(Queretaro)	16.9	27.1	33.9	22.4	16.8	6.7	-0.4	2.5	5.1	5.7	
CNMP	(Panama)	-29.5	-33.5	-42.7	-41.6	-44.8	-	-46.7	3.0	5.2	6.0	
DLR	(Oberpfaffenhofen)	32.3	39.0	34.2	28.1	24.6	22.7	9.3	0.4	5.1	5.2	
DMDM	(Belgrade)	-47.4	-50.5	-48.2	-42.2	-40.1	-37.6	-21.3	2.0	7.1	7.4	
DTAG	(Frankfurt/M)	-545.3	-540.3	-526.4	-510.8	-484.5	-468.4	-441.5	0.4	10.0	10.0	
EIM	(Thessaloniki)	5.0	-0.9	2.8	0.1	1.3	-2.3	6.6	3.5	5.2	6.2	
HKO	(Hong Kong)	56.8	58.8	64.5	71.6	88.8	93.1	97.7	2.5	5.2	5.7	
IFAG	(Wetzell)	-58.6	-59.1	-54.7	-49.5	-43.9	-40.4	-36.3	0.4	5.1	5.1	
IGNA	(Buenos Aires)	-	-	-	-	-	-	-	-	-	-	
INPL	(Jerusalem)	-	-	-	-	-	-	-	-	-	-	
INTI	(Buenos Aires)	137.8	210.6	169.2	148.2	129.3	80.6	42.4	4.0	20.0	20.4	
IPQ	(Caparica)	-15.3	-19.6	-17.1	-22.5	-29.3	-28.0	-37.8	1.0	7.0	7.1	(1)
IT	(Torino)	1.7	1.2	-0.7	-0.9	-1.0	-0.7	0.1	0.6	1.7	1.8	
JATC	(Lintong)	-12.8	-4.5	-7.2	-15.0	-14.9	-6.4	-7.6	1.5	5.0	5.2	
JV	(Kjeller)	-39913.9	-39979.1	-40057.8	-40133.6	-40193.6	-40251.1	-40308.1	5.0	20.0	20.7	
KIM	(Serpong-Tangerang)	-119.9	-132.8	-124.2	-118.9	-118.8	-117.6	-129.6	3.0	20.0	20.2	
KRIS	(Daejeon)	-9.0	5.5	-13.8	-9.2	-1.0	-11.1	-10.3	0.4	5.0	5.1	
KZ	(Astana)	-5.9	-12.7	-14.0	-11.8	-8.5	-10.6	-9.3	2.0	20.0	20.1	
LT	(Vilnius)	1263.2	1284.8	1287.2	1303.6	1284.8	-	207.2	2.0	5.2	5.5	(2)
LV	(Riga)	3834.4	3835.1	3831.6	3824.8	3812.8	3799.0	3782.7	0.8	7.1	7.2	
MIKE	(Espoo)	9.9	9.1	8.0	7.7	6.6	7.2	8.1	0.4	7.1	7.1	

Date 2010	0h UTC	SEP 30	OCT 5	OCT 10	OCT 15	OCT 20	OCT 25	OCT 30	Uncertainty/ns			Notes
MJD		55469	55474	55479	55484	55489	55494	55499	u_A	u_B	u	
Laboratory k		[UTC-UTC(k)]/ns										
MKEH (Budapest)		-41167.0	-41369.7	-41577.7	-41799.6	-41993.1	-42202.4	-42401.7	4.0	20.0	20.4	
MSL (Lower Hutt)		217.7	289.4	366.1	448.3	492.2	528.7	569.4	1.0	20.0	20.0	
NAO (Mizusawa)		-2.5	-3.7	-5.6	-6.2	-0.9	-12.0	-10.8	3.0	19.8	20.0	
NICT (Tokyo)		7.9	9.2	9.5	11.3	9.3	10.5	10.8	0.3	4.6	4.6	
NIM (Beijing)		-29.6	-29.2	-30.2	-28.5	-25.9	-21.4	-17.3	0.7	5.1	5.2	
NIMB (Bucharest)		-296.4	-294.9	-264.4	-251.6	-257.7	-271.1	-255.3	2.0	20.0	20.1	
NIMT (Pathumthani)		-525.9	-496.6	-460.6	-432.0	-399.6	-368.6	-332.5	1.0	20.0	20.0	
NIS (Cairo)		42.8	41.1	42.7	38.9	34.4	39.4	34.3	0.8	7.1	7.2	
NIST (Boulder)		-3.3	-4.0	-4.6	-3.6	-3.7	-2.9	-1.6	0.4	4.9	4.9	
NMIJ (Tsukuba)		-0.5	-1.5	-2.4	-3.0	-2.0	-0.1	2.1	0.4	5.0	5.1	
NMLS (Sepang)		-1042.9	-1075.3	-1101.3	-1132.4	-1161.7	-1200.9	-1234.4	2.0	20.0	20.1	
NPL (Teddington)		16.1	11.6	9.2	8.4	5.7	1.8	-	4.0	5.2	6.5	
NPLI (New-Delhi)		-12.6	-12.0	-15.1	-8.5	-15.6	-3.2	-12.5	2.5	7.1	7.5	
NRC (Ottawa)		95.9	90.9	89.4	82.4	81.1	75.5	63.6	0.4	5.1	5.1	
NRL (Washington DC)		6.7	5.7	5.7	2.1	-1.3	0.1	-0.6	0.4	5.2	5.2	
NTSC (Lintong)		5.4	9.7	10.1	10.1	13.4	18.2	6.6	1.4	4.9	5.1	
ONBA (Buenos Aires)		-3801.1	-3832.9	-3853.2	-3875.5	-3885.8	-3913.5	-3947.0	4.0	5.1	6.5	
ONRJ (Rio de Janeiro)		6.7	7.7	2.2	-7.2	2.2	8.6	8.1	3.9	19.7	20.1	
OP (Paris)		34.0	47.1	38.1	30.4	22.5	15.9	0.1	0.7	1.6	1.7	
ORB (Bruxelles)		27.1	-	28.3	31.9	35.0	37.8	43.3	0.4	5.2	5.2	
PL (Warszawa)		-12.6	-7.6	-9.4	-9.1	-22.0	-21.3	-18.5	1.5	5.1	5.3	
PTB (Braunschweig)		-2.3	-2.8	-2.8	-1.9	-2.4	-2.3	-3.0	0.2	1.3	1.3	
ROA (San Fernando)		17.3	18.9	21.0	24.1	24.7	25.1	24.2	0.6	5.1	5.2	
SCL (Hong Kong)		24.9	34.9	36.6	43.2	47.0	46.6	47.8	3.0	10.0	10.5	
SG (Singapore)		31.0	32.5	29.6	24.9	23.2	20.1	14.4	0.4	5.2	5.2	
SIQ (Ljubljana)		-231.6	-231.9	-251.9	-263.6	-287.5	-297.3	-298.7	5.0	20.0	20.6	
SMD (Bruxelles)		5.7	0.8	-12.4	-13.7	-3.1	3.3	1.6	1.5	19.7	19.8	
SMU (Bratislava)		-139.5	-125.8	-120.4	-113.0	-95.8	-84.4	-76.3	1.5	20.0	20.1	
SP (Boras)		-2.6	-5.6	-7.6	-6.0	-3.9	-3.7	-2.9	0.6	1.6	1.7	
SU (Moskva)		-6.2	-7.0	-6.7	-3.7	-1.2	2.1	4.9	1.5	5.0	5.3	
TCC (Concepcion)		797.1	810.3	816.4	833.7	846.0	849.1	869.1	0.4	19.9	19.9	
TL (Chung-Li)		-10.8	-9.4	-12.8	-14.3	-14.4	-15.3	-13.8	0.4	4.9	4.9	
TP (Praha)		21.1	24.8	23.6	27.5	22.9	18.1	18.4	0.4	5.1	5.1	
UA (Kharkov)		-	-	-	-	-39.2	-50.1	-59.4	1.5	20.0	20.1	(3)
UME (Gebze-Kocaeli)		-587.4	-607.3	-626.2	-647.0	-657.6	-663.9	-678.8	1.5	7.1	7.2	
USNO (Washington DC)		1.3	1.4	0.3	0.5	0.7	1.1	0.8	0.5	2.4	2.4	
VMI (Ha Noi)		37.9	21.6	15.2	8.5	-0.3	4.1	-1.2	1.0	20.0	20.1	
VSL (Delft)		2.8	-8.6	-10.3	-4.7	-7.2	-4.6	-4.7	0.8	1.6	1.8	
ZA (Pretoria)		-1987.9	-2077.7	-2157.3	-2209.6	-2272.2	-2342.8	-2439.4	1.5	19.9	20.0	

- Notes on section 1:

- (1) IPQ : Time step of UTC(IPQ) of +15 ns on MJD 55494.2.
- (2) LT : Time step of UTC(LT) of +1200 ns on MJD 55494.0.
- (3) UA : Time step of UTC(UA) of +100 ns on MJD 55473.0.
Change of receiver on MJD 55487.

2 - International Atomic Time TAI and Local atomic time scales TA(k). Computed values of [TAI-TA(k)].

Date 2010	0h UTC	SEP 30	OCT 5	OCT 10	OCT 15	OCT 20	OCT 25	OCT 30	
MJD		55469	55474	55479	55484	55489	55494	55499	
Laboratory k		[TAI-TA(k)]/ns							
CH (Bern)		44872.7	44813.7	44758.2	44702.8	44648.4	44593.8	44537.7	
F (Paris)		167877.2	167876.0	167871.8	167869.1	167864.2	167864.3	167864.1	
IT (Torino)		96441.5	96580.3	96718.9	96856.7	96995.3	97133.5	97270.6	
JATC (Lintong)		-48527.6	-48552.0	-48580.7	-48609.2	-48634.7	-48657.1	-48683.5	
KRIS (Daejeon)		33978.6	34052.6	34074.8	34132.7	34197.5	34231.6	34282.2	
NICT (Tokyo)		-148.0	-149.9	-149.5	-151.5	-152.1	-152.9	-153.1	
NIST (Boulder)		-45353906.0	-45354099.7	-45354293.3	-45354485.9	-45354680.0	-45354873.2	-45355065.9	
NRC (Ottawa)		27869.4	27839.3	27812.3	27779.9	27753.3	27722.3	27685.1	
NTSC (Lintong)		11084.9	11109.0	11130.3	11153.2	11176.5	11200.8	11223.9	
ONRJ (Rio de Janeiro)		-8116.1	-8148.7	-8176.7	-8207.9	-8238.8	-8267.2	-8298.3	
PL (Warszawa)		-7693.6	-7721.0	-7751.6	-7780.7	-7809.6	-7836.2	-7858.5	
PTB (Braunschweig)		-329401.2	-329396.8	-329388.2	-329379.3	-329369.2	-329363.0	-329352.2	
SG (Singapore)		7002.0	7013.5	7022.6	7030.9	7041.2	7051.1	7059.4	
SU (Moskva)		27266359.3	27266503.2	27266648.2	27266793.8	27266937.5	27267082.1	27267227.5	(1)
TL (Chung-Li)		-562.9	-565.5	-562.3	-562.5	-563.8	-561.8	-559.3	
USNO (Washington DC)		-35072835.4	-35073131.8	-35073429.2	-35073725.4	-35074022.4	-35074319.4	-35074617.1	

- Note on section 2:

- (1) SU : Listed values are TAI-TA(SU) - 2.80 seconds.

3 - Difference between the normalized frequencies of EAL (free atomic time scale) and TAI.

	Interval of validity	$f(EAL)-f(TAI)$	
Steering correction	55469 - 55499	6.619×10^{-13}	(2010 SEP 30 - 2010 OCT 30)
New correction	55499 - 55529	6.612×10^{-13}	(2010 OCT 30 - 2010 NOV 29)
New correction foreseen	55529 - 55559	6.605×10^{-13}	(2010 NOV 29 - 2010 DEC 29)

4 - Duration of the TAI scale interval.

TAI is a realization of coordinate time TT. The following tables give the fractional deviation d of the scale interval of TAI from that of TT (the SI second on the geoid), i.e. the fractional frequency deviation of TAI with the opposite sign: $d = -y_{TAI}$. In this section, a frequency over a time interval is defined as the ratio of the end-point phase difference to the duration of the interval. Whenever needed, the instability of EAL should be expressed as the quadratic sum of three components with τ in days: (1) a white frequency noise of $2.0 \times 10^{-15} / \sqrt{\tau}$, (2) a flicker frequency noise of 0.4×10^{-15} and (3) a random walk frequency noise of $1.0 \times 10^{-16} \times \sqrt{\tau}$. The relation between EAL and TAI is given in *Circular T* and the *BIPM Annual Report on Time Activities*.

In the first table, d is obtained, on the given periods of estimation by comparison of the TAI frequency with that of the given individual Primary Frequency Standards (PFS). In this table: u_A is the uncertainty originating in the instability of the PFS, u_B is the combined uncertainty from systematic effects, $u_{1/Lab}$ is the uncertainty in the link between the PFS and the clock participating to TAI, including the uncertainty due to the dead-time, $u_{1/TAI}$ is the uncertainty in the link to TAI, u is the quadratic sum of all four uncertainty values. Ref(u_B) is a reference giving information on the values of u_B or is the *Circular T* where the reference was first given. $u_B(Ref)$ is the u_B value stated in this references. Note that all uncertainties may vary over time and that the current u_B values are generally not the same as the peer reviewed values given in Ref(u_B). See "<http://www.bipm.org/jsp/en/TimeFtp.jsp>" for previous issues of *Circular T* and individual Reports of Evaluation of Primary Frequency Standards that explain changes in uncertainties. All values are expressed in 10^{-15} and are valid only for the stated period of estimation.

Standard	Period of Estimation	d	u_A	u_B	$u_{1/Lab}$	$u_{1/TAI}$	u	Ref(u_B)	$u_B(Ref)$	Note
PTB-CS1	55469 55499	-1.93	6.00	8.00	0.00	0.13	10.00	T148	8.	(1)
SYRTE-F01	55469 55494	5.79	0.30	0.48	0.14	0.54	0.79	T227	0.72	(2)
SYRTE-F02	55479 55494	6.88	0.30	0.41	0.12	0.85	1.00	T227	0.65	(2)
PTB-CSF1	55484 55499	7.36	0.24	0.76	0.02	0.24	0.83	T162	1.40	(3)

Notes:

- (1) Continuously operating as a clock participating to TAI
- (2) Report 02 NOV. 2010 by LNE-SYRTE
- (3) Report 03 NOV. 2010 by PTB

Erratum *Circular T* 273:

Standard	Period of Estimation	d	u_A	u_B	$u_{1/Lab}$	$u_{1/TAI}$	u	Ref(u_B)	$u_B(Ref)$	Note
IT-CsF1	55449 55464	8.34	0.40	0.90	0.20	0.73	1.24	T233	0.80	

The second table gives the BIPM estimate of d , based on all available PFS measurements over the period MJD 55109-55499, taking into account their individual uncertainties and characterizing the instability of EAL as noted above. u is the computed standard uncertainty of d

Period of estimation	d	u
55469-55499	6.4×10^{-15}	0.5×10^{-15} (2010 SEP 30 - 2010 OCT 30)

5 - Relations of UTC and TAI with GPS time and GLONASS time.

$$\begin{aligned}
 [UTC-GPS \text{ time}] &= -15 \text{ s} + C_0, & [TAI-GPS \text{ time}] &= 19 \text{ s} + C_0, & \text{global uncertainty is of order 10 ns.} \\
 [UTC-GLONASS \text{ time}] &= 0 \text{ s} + C_1, & [TAI-GLONASS \text{ time}] &= 34 \text{ s} + C_1, & \text{global uncertainty is of order hundreds ns.}
 \end{aligned}$$

The C_0 values provide a realization of GPS time, as obtained using the values $[UTC-UTC(OP)]$ and the GPS data taken at the Paris Observatory, corrected for IGS precise orbits, clocks and ionosphere maps. The C_1 values provide a realization of GLONASS time, as obtained using the values $[UTC-UTC(AOS)]$ and the GLONASS data taken at the Astrogeodynamical Observatory Borowiec (AOS). N_0 and N_1 are the numbers of measurements, when N_0 or N_1 is 0, the corresponding values of C_0 or C_1 are interpolated.

The standard deviations σ_0 and σ_1 characterize the dispersion of individual measurements. The actual uncertainty of user's access to GPS and GLONASS times may differ from these values. For this circular, $\sigma_0 = 3.1 \text{ ns}$, $\sigma_1 = 7.2 \text{ ns}$

Date 2010	0h UTC	MJD	C_0/ns	N_0	C_1/ns	N_1
	SEP 30	55469	1.3	43	-127.2	85
	OCT 1	55470	2.0	43	-125.3	80
	OCT 2	55471	2.0	43	-129.2	81
	OCT 3	55472	5.3	43	-136.7	90
	OCT 4	55473	0.4	43	-142.6	73
	OCT 5	55474	-3.1	40	-142.2	79
	OCT 6	55475	-9.3	41	-140.8	80
	OCT 7	55476	-12.7	41	-141.3	82
	OCT 8	55477	-16.4	42	-140.4	81
	OCT 9	55478	-15.1	42	-140.7	83
	OCT 10	55479	-12.2	43	-140.9	86
	OCT 11	55480	-11.4	39	-140.0	86
	OCT 12	55481	-10.6	39	-143.3	89
	OCT 13	55482	-9.6	39	-148.3	86
	OCT 14	55483	-6.2	43	-150.1	86
	OCT 15	55484	-4.7	40	-149.9	88
	OCT 16	55485	-1.6	43	-150.7	80
	OCT 17	55486	-0.5	43	-151.7	89
	OCT 18	55487	-4.3	41	-152.7	80
	OCT 19	55488	-2.6	42	-155.2	87
	OCT 20	55489	-3.1	41	-156.1	84
	OCT 21	55490	-5.3	41	-154.6	85
	OCT 22	55491	-7.1	41	-153.0	84
	OCT 23	55492	-8.8	41	-152.4	84
	OCT 24	55493	-11.4	41	-151.9	85
	OCT 25	55494	-10.9	37	-152.7	89
	OCT 26	55495	-10.0	42	-153.9	79
	OCT 27	55496	-7.9	28	-159.0	89
	OCT 28	55497	-7.2	14	-167.2	88
	OCT 29	55498	-4.9	43	-167.7	87
	OCT 30	55499	-4.0	43	-163.0	81

6 - Time links used for the computation of TAI and their uncertainties.

The time links used in the elaboration of this *Circular T* are listed in this section. The technique for the link is indicated as follows: GPS SC for GPS all-in-view single-channel C/A data; GPS MC for GPS all-in-view multi-channel C/A data; GPS P3 for GPS all-in-view multi-channel dual-frequency P code data; GPS PPP for GPS Precise Point Positioning technique; GPS GT for 'GPS time' observations; GLN MC for GLONASS common-view multi-channel C/A data; INT LK for internal cable link and TWSTFT for two-way satellite time and frequency transfer data.

For each link, the following uncertainties are provided: u_A is the statistical uncertainty evaluated by taking into account the level of phase noise in the raw data, the interpolation interval between data points and the effects with typical duration between 5 and 30 days. u_B is the estimated uncertainty on the calibration.

The calibration type of the link is indicated as: GPS EC for GPS equipment calibration; TW EC for two-way equipment calibration; LC (technique) for a link calibrated using 'technique'; BC (technique) for a link calibrated using 'technique' to transfer a past equipment calibration through a discontinuity of link operation. DIC is used for direct internal calibration.

The calibration dates indicate: the most recent calibration results for the two laboratories in the case of EC and the most recent calibration of the link in the case of LC and BC, NA stands for not available, in this case estimated values are provided

Link	Type	u_A /ns	u_B /ns	Calibration Type	Calibration Dates
AOS /PTB	TWSTFT	0.5	5.0	BC(GPS MC)	2008 May
APL /PTB	GPS MC	1.5	5.0	GPS EC/GPS EC	2003 Dec/2006 Sep
AUS /PTB	GPSPPP	0.3	5.0	LC(GPS MC)	2009 Nov
BEV /PTB	GPS MC	1.5	3.0	BC(TWSTFT)	2008 Jan
BIM /PTB	GPS MC	2.0	7.0	GPS EC/GPS EC	2007 Nov
BIRM/PTB	GPS MC	2.0	20.0	NA /GPS EC	NA /2006 Sep
BY /PTB	GPS MC	2.0	7.0	GPS EC/GPS EC	2008 Jun/2006 Sep
CAO /PTB	GPS MC	1.5	7.0	GPS EC/GPS EC	2004 Nov/2006 Sep
CH /PTB	TWSTFT	0.6	1.0	LC(TWSTFT)/BC(GPS PPP)	2008 Sep/2009 Aug
CNM /PTB	GPS MC	2.5	5.0	BC(GPS SC)	2008 May
CNMP/PTB	GPS MC	3.0	5.0	GPS EC/GPS EC	2004 May/2006 Sep
DLR /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2007 Feb/2004 Aug
DMDM/PTB	GPS MC	2.0	7.0	GPS EC/GPS EC	2007 Jan/2006 Sep
DTAG/PTB	GPSPPP	0.3	10.0	LC(GPS MC)	2009 Jul
EIM /PTB	GPS MC	3.5	5.0	GPS EC/GPS EC	2007 May/2003 Aug
HKO /PTB	GPS MC	2.5	5.0	GPS EC/GPS EC	2004 Sep/2006 Sep
IFAG/PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2003 Jun/2004 Aug
IGNA/PTB	NA				
INPL/PTB	NA				
INTI/PTB	GPS MC	4.0	20.0	NA /GPS EC	NA /2006 Sep

Link	Type	u_A /ns	u_B /ns	Calibration Type	Calibration Dates
IPQ /PTB	TWSTFT	1.0	7.0	LC(GPS MC)	2010 Aug
IT /PTB	TWSTFT	0.6	1.2	LC(TWSTFT)/BC(GPS PPP)	2008 Sep/2009 Aug
JATC/NTSC	INT LK	0.2	1.0	DIC	/2006 Sep
JV /PTB	GPS GT	5.0	20.0	NA /GPS EC	NA /2003 Aug
KIM /PTB	GPS MC	3.0	20.0	NA /GPS EC	NA /2006 Sep
KRIS/PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2005 Aug/2004 Aug
KZ /PTB	GPS MC	2.0	20.0	NA /GPS EC	NA /2006 Sep
LT /PTB	GPS MC	2.0	5.0	GPS EC/GPS EC	2006 Oct/2006 Sep
LV /PTB	GPS P3	0.8	7.0	LC(GPS MC)	2010 Jun
MIKE/PTB	GPSPPP	0.3	7.0	NA /GPS EC	NA /2004 Aug
MKEH/PTB	GPS SC	4.0	20.0	NA /GPS EC	NA /2006 Sep
MSL /PTB	GPS P3	1.0	20.0	NA /GPS EC	NA /2004 Aug
NAO /PTB	GPS MC	3.0	20.0	NA /GPS EC	NA /2006 Sep
NICT/PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2005 Jun/2004 Aug
NIM /PTB	GPS P3	0.7	5.0	GPS EC/GPS EC	2009 Dec/2004 Aug
NIMB/PTB	GPS MC	2.0	20.0	NA /GPS EC	NA /2006 Sep
NIMT/PTB	GPS P3	1.0	20.0	NA /GPS EC	NA /2004 Aug
NIS /PTB	GPS P3	0.8	7.0	LC(GPS MC)	2010 Jun
NIST/PTB	TWSTFT	0.3	5.0	LC(TWSTFT)/BC(GPS PPP)	2005 May/2009 Aug
NMIJ/PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2002 Apr/2004 Aug
NMLS/PTB	GPS MC	2.0	20.0	NA /GPS EC	NA /2006 Sep
NPL /PTB	GPS MC	4.0	5.0	LC(GPS PPP)	2010 Sep
NPLI/PTB	GPS MC	2.5	7.0	GPS EC/GPS EC	2005 Jul/2006 Sep
NRC /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2003 Nov/2004 Aug
NRL /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2002 May/2004 Aug
NTSC/PTB	GPS MC	1.5	5.0	GPS EC/GPS EC	2004 Sep/2006 Sep
ONBA/PTB	GPS MC	4.0	5.0	GPS EC/GPS EC	2004 Jul/2006 Sep
ONRJ/PTB	GPS MC	4.0	20.0	NA /GPS EC	NA /2006 Sep
OP /PTB	TWSTFT	0.7	1.1	LC(TWSTFT)/BC(GPS PPP)	2008 Sep/2009 Aug
ORB /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2003 Jul/2004 Aug
PL /PTB	GPS MC	1.5	5.0	GPS EC/GPS EC	2006 Oct/2006 Sep
ROA /PTB	TWSTFT	0.6	5.0	LC(TWSTFT)/BC(GPS PPP)	2005 May/2009 Aug
SCL /PTB	GPS MC	3.0	10.0	LC(GPS SC)	1993 May
SG /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2010 Mar/2004 Aug
SIQ /PTB	GPS SC	5.0	20.0	NA /GPS EC	NA /2003 Aug
SMD /PTB	GPS MC	1.5	20.0	NA /GPS EC	NA /2006 Sep
SMU /PTB	GPS MC	1.5	20.0	NA /GPS EC	NA /2006 Sep
SP /PTB	TWSTFT	0.6	1.0	LC(TWSTFT)/BC(GPS PPP)	2006 Mar/2009 Aug
SU /PTB	GLN MC	1.5	5.0	LC(GPS MC)	2009 May
TCC /PTB	GPSPPP	0.3	20.0	NA /GPS EC	NA /2004 Aug
TL /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2005 May/2004 Aug
TP /PTB	GPSPPP	0.3	5.0	GPS EC/GPS EC	2009 Feb/2004 Aug
UA /PTB	GPS MC	1.5	20.0	NA /GPS EC	NA /2006 Sep
UME /PTB	GPS MC	1.5	7.0	GPS EC/GPS EC	2005 Dec/2006 Sep
USNO/PTB	TWSTFT	0.6	3.0	BC(TW X)/BC(GPS PPP)	2005 May/2010 Jan
VMI /PTB	GPS P3	1.0	20.0	NA /GPS EC	NA /2004 Aug
VSL /PTB	TWSTFT	0.8	1.0	LC(TWSTFT)/BC(GPS PPP)	2006 Mar/2009 Aug
ZA /PTB	GPS P3	1.5	20.0	NA /GPS EC	NA /2004 Aug