

# EXPLANATORY SUPPLEMENT OF BIPM *CIRCULAR T*

---

This document describes the contents of the sections in BIPM *Circular T* from June 2020.

For automatic data extraction, a *Circular T* format description file is available at [ftp://ftp2.bipm.org/pub/tai/publication/notes/cirt\\_format\\_v0.2.txt](ftp://ftp2.bipm.org/pub/tai/publication/notes/cirt_format_v0.2.txt).

The issues of BIPM *Circular T* are available at the BIPM website at <https://www.bipm.org/en/bipm-services/timescales/time-ftp/introduction.html> ; data used in the calculation of each *Circular T* are available at <http://www.bipm.org/fr/bipm-services/timescales/time-ftp/data.html> .

In *Circular T*, all uncertainties are expressed with a coverage factor  $k = 1$ .

## Section 1

### Difference between UTC and its local realizations UTC(k) and corresponding uncertainties

This section gives the values of  $[UTC-UTC(k)]$  (in ns) at five-day intervals on MJD ending by 4 and 9, at 0 h UTC for local realizations of UTC maintained at contributing laboratories "k" and their respective uncertainties, valid for the month [1]. Notes on this section provide relevant information relating to a result.

[1] Lewandowski W., Matsakis D., Panfilo G., Tavella P., The evaluation of uncertainties in  $[UTC-UTC(k)]$ , *Metrologia*, 2006, 43(3), 278-286

## Section 2

### Difference between the normalized frequencies of EAL and TAI

This section gives the values of the difference between the normalized frequencies of EAL (free atomic time scale) and TAI for the interval covered by the current *Circular T* as well as those for the following two months. They indicate if a steering correction of the frequency of EAL has been applied and/or is foreseen necessary for preserving the accuracy of TAI.

## Section 3

### Duration of the TAI scale interval $d$

TAI is a realization of coordinate time TT. The tables give the fractional deviation  $d$  of the scale interval of TAI from that of TT (in practice, the SI second on the geoid), i.e. the fractional frequency deviation of TAI with the opposite sign:  $d = -y_{\text{TAI}}$ . In this section, a frequency over a time interval is defined as the ratio of the end-point phase difference to the duration of the interval. Whenever needed, the instability of EAL should be expressed as the quadratic sum of three components with  $\tau$  in days:

1. a white frequency noise of  $1.7 \times 10^{-15} / \sqrt{\tau}$ ,
2. a flicker frequency noise of  $0.35 \times 10^{-15}$ ,
3. a random walk frequency noise of  $0.2 \times 10^{-16} \times \sqrt{\tau}$ .

The relation between EAL and TAI is given in Section 2 of *Circular T* and in the *BIPM Annual Report on Time Activities*.

In the first table,  $d$  is obtained, on the given periods of estimation by comparison of the TAI frequency with that of the given individual Primary and Secondary Frequency Standards (PFS/SFS).

In this table:

- $u_A$  is the uncertainty originating in the instability of the standard,
- $u_B$  is the combined uncertainty from systematic effects,
- $u_{A/lab}$  and  $u_{B/lab}$  represent the uncertainty in the link between the standard and the clock participating to TAI, respectively from statistical fluctuations including the uncertainty due to the dead-time for  $u_{A/lab}$ , and from systematic effects for  $u_{B/lab}$ ,
- $u_{I/TAI}$  is the uncertainty in the link to TAI,
- $u$  is the quadratic sum of all five uncertainty values,
- **Ref( $u_B$ )** is a reference giving information on the values of  $u_B$  or is the *Circular T* where the reference was first given,
- **$u_B$ (Ref)** is the  $u_B$  value stated in this reference,
- **Uptime** is the percentage of the period of estimation when the frequency of the standard is actually used to obtain the reported frequency; it is the complement of the dead-time used for  $u_{A/lab}$ ,
- **Lastrep** is the Circular T number where the standard was last reported,
- **Nrep3y** is the number of reports of the standard published in the preceding 36 months,
- **Steer** indicates whether the standard has been approved for TAI steering by the CCTF working group on primary and secondary frequency standards.

Note that all uncertainties may vary over time and that the current  $u_B$  values are generally not the same as the peer reviewed values given in Ref( $u_B$ ).

See <http://www.bipm.org/jsp/en/TimeFtp.jsp> for previous issues of *Circular T* and individual Reports of Evaluation of Primary and Secondary Frequency Standards that explain changes in uncertainties.

For the SFS,  $u_{srep}$  represents the recommended uncertainty of the secondary representation of the second and **Ref( $u_s$ )** provides the reference for the frequency of the transition and its uncertainty  $u_{srep}$ , these two fields are not applicable to PFS.

All values are expressed in  $10^{-15}$  and are valid only for the stated period of estimation.

The second table gives the BIPM estimate of  $d$ , based on all available PFS and SFS measurements over the indicated period, taking into account their individual uncertainties and characterizing the instability of EAL as noted above.  $u$  is the computed standard uncertainty of  $d$ .

Note that a plot summarizing all PFS and SFS evaluations since Circular T190 may be found at [https://webtai.bipm.org/database/show\\_psfs.html](https://webtai.bipm.org/database/show_psfs.html).

## Section 4

### Relations of UTC and TAI with predictions of UTC(k) disseminated by GNSS,

Global Navigation Satellite Systems (GNSS) broadcast predictions of UTC. [*UTC(USNO)\_GPS*] and [*UTC(SU)\_GLONASS*] are, respectively, UTC(USNO) and UTC(SU) as predicted by USNO and SU and disseminated by GPS and GLONASS respectively.

$$[UTC-UTC(USNO)_GPS] = C_0',$$

$$[TAI-UTC(USNO)_GPS] = XX \text{ s} + C_0', \text{ global uncertainty is of the order of } 10 \text{ ns.}$$

$$[UTC-UTC(SU)_GLONASS] = C_1',$$

$$[TAI-UTC(SU)_GLONASS] = XX \text{ s} + C_1', \text{ global uncertainty is of the order of hundreds ns.}$$

The  $XX$  value is the difference  $[TAI-UTC]$  as an integer number of seconds. It may change by insertion of positive or negative leap seconds under the responsibility of the IERS, see the IERS website : <https://hpiers.obspm.fr/eoppc/bul/bulc/UTC-TAI.history>.

The  $C_0'$  values provide realizations of the prediction of UTC(USNO) broadcast by GPS, as obtained using the values  $[UTC-UTC(OP)]$  and the GPS data taken at the Paris Observatory, corrected for IGS precise orbits, clocks and ionosphere maps.

The  $C_1'$  values provide realizations of the prediction of UTC(SU) broadcast by GLONASS, as obtained using the values  $[UTC-UTC(AOS)]$  and the GLONASS data taken at the Astrogeodynamical Observatory Borowiec (AOS).

$N_0'$  and  $N_1'$  are the number of 13-minute CGGTTS intervals; when  $N_0'$  or  $N_1'$  is 0, the corresponding values in the table are interpolated.

The standard deviations  $\sigma_0'$  and  $\sigma_1'$  characterize the dispersion of individual measurements. The actual uncertainty of users' access to GPS and GLONASS times may differ from the published values.

## Section 5

### Time links used for the computation of TAI, calibrations information and corresponding uncertainties

This section provides information on the time links used in the elaboration of each *Circular T*, including equipment and calibration identifiers, uncertainties and alignment corrections applied by the BIPM, if any. Description of the plots content is available in section 2.3 of the document [ftp://ftp2.bipm.org/pub/tai/timelinks/lkc/ReadMe\\_LinkComparison\\_ftp\\_v11.pdf](ftp://ftp2.bipm.org/pub/tai/timelinks/lkc/ReadMe_LinkComparison_ftp_v11.pdf).

The first table includes links formed with station-based GNSS techniques indicated as follows:

- **GPS MC** for GPS all-in-view multi-channel C/A data,
- **GPS P3** for GPS all-in-view multi-channel dual-frequency P code data,
- **GPSPPP** for GPS Precise Point Positioning technique,
- **GLN MC** for GLONASS common-view multi-channel C/A data,
- **GPSGLN** for the combination of GPS MC and GLN MC.

The second table includes link-based techniques, indicated as

- **TWSTFT** for two-way satellite time and frequency transfer,
- **TWGPPP** for the combined smoothing of TWSTFT and GPS PPP,

For a link, the equipment at each laboratory is designated by its unique identifier (6-character for TWSTFT ground station).

- **Cal\_ID** is the calibration identifier of the campaign where the equipment/link has been calibrated [1],
- **NC** stands for no calibration,
- **NA** stands for no availability of the calibration report,
- **NC\_AI** indicates that a correction has been applied for aligning the current link to another link previously used, non-calibrated,
- **NA\_AI** indicates that a correction has been applied for aligning the current link to another link previously used and calibrated, for which the calibration report is not available,
- **NL** indicates that no time transfer data was available for this *Circular T* period,

- ***uStb*** is the standard uncertainty representing the link instability and accounting for measurement noise and random effects with typical duration between 1 and 30 days,
- ***uCal*** represents the total uncertainty from calibration, derived from the original equipment/link calibration uncertainty and also including components for aging and for alignment when appropriate. In the case of links involving TWSTFT the standard measurement uncertainty of ESDVAR (ESIG) is also included, if applicable.  
A value of 20 ns is conventionally assigned to  $u_{CAL}$  for non-calibrated equipment/links; this value does not represent the uncertainty of the link, which cannot be evaluated,
- ***uAg*** is the uncertainty accounting for calibration aging [2] with a value of 10 ns assigned to calibrations older than 10 years,
- ***Al*** is the link alignment correction applied if necessary by the BIPM on ***YYMM*** (year and month), the conventional uncertainty increment for an alignment is 1 ns.

For the calibration uncertainty of GNSS equipment prior to 2014, refer to the BIPM guidelines for GNSS calibrations [3], sub-section A1.

[1] BIPM calibration information can be found in: <http://www.bipm.org/jsp/en/TimeCalibrations.jsp>

[2] Jiang Z., Arias F., Lewandowski W., Petit G. , BIPM Calibration Scheme for UTC Time Links, Proc. *2011 Joint Conference of IFCS and EFTF*, pp 1064-1069

[3] [BIPM guidelines for GNSS calibration](#)